

CENTURACORES

Nanocrystalline Transformer Cores

<https://centuracores.com/products/ccnt-050-032-015-hfwh/>

Product datasheet: CCNT-050-032-015-HFWH

Product information

Nanocrystalline toroidal core 50x32x15 mm

Bare size: 50x32x15 mm

Finish: White PBT Class B 130C

CCNT-050-032-015-HFWH is a 50x32x15 mm nanocrystalline toroidal core for three-phase drive EMI filters, solar/wind inverter chokes, and industrial SMPS filters. Its nanocrystalline HF characteristic supports common-mode and EMI filter designs where impedance and winding window matter as much as size. Choose this size when the filter or choke needs this window and OD, not the next larger footprint.

Bare core dimensions

Outer diameter (OD): 50 mm

Inner diameter (ID): 32 mm

Height (H): 15 mm

Cased / finished dimensions

Outer diameter (OD): 53.9 mm

Inner diameter (ID): 28.9 mm

Height (H): 18.7 mm

Tolerance: 0.5mm

Size marking on the case is the bare core dimension, not the cased or finished size.

Magnetic properties

Effective area A_e : 1.1 cm²

Mean path length L_e : 12.87 cm

AL @ 10kHz, 2mT: 90 uH/T²

AL @ 100kHz, 2mT: 36 uH/T²

Saturation B_s : 1.25 Tesla

Initial permeability μ_i : 80000

Curie temperature: 560 C

Operating temperature: -40 deg C to +130 deg C

Net weight: 103 g

Applications

- three-phase drive EMI filters
- solar/wind inverter chokes
- industrial SMPS filters
- higher-power UPS filters
- three-phase VFD/industrial drive common-mode filters
- solar/wind inverter output chokes
- industrial SMPS EMI suppression cores
- higher-power (300–1000W class) UPS EMI filters