

CENTURACORES

Nanocrystalline Transformer Cores

<https://centuracores.com/products/ccnt-050-032-015-mfbl/>

Product datasheet: CCNT-050-032-015-MFBL

Product information

Nanocrystalline toroidal core 50x32x15 mm

Bare size: 50x32x15 mm

Finish: Blue PBT Class B 130C

CCNT-050-032-015-MFBL is a 50x32x15 mm nanocrystalline toroidal core for high-current metering CTs, medium-frequency transformers, and protective relay CTs. Its 32 mm inner diameter supports practical secondary windings, while high-permeability nanocrystalline material helps achieve useful magnetizing inductance at low turns. Choose this size when winding window, magnetic area, and envelope must stay in balance for the target current or VA.

Bare core dimensions

Outer diameter (OD): 50 mm

Inner diameter (ID): 32 mm

Height (H): 15 mm

Cased / finished dimensions

Outer diameter (OD): 53.9 mm

Inner diameter (ID): 28.9 mm

Height (H): 18.7 mm

Tolerance: 0.5mm

Size marking on the case is the bare core dimension, not the cased or finished size.

Magnetic properties

Effective area A_e : 1.1 cm²

Mean path length L_e : 12.87 cm

AL @ 1kHz: 160 uH/T²

AL @ 10kHz, 2mT: 65 uH/T²

AL @ 100kHz, 2mT: 22 uH/T²

Saturation B_s : 1.25 Tesla

Initial permeability μ_i : 80000

Curie temperature: 560 C

Operating temperature: -40 deg C to +130 deg C

Net weight: 117 g

Applications

CenturaCores product catalog | centuracores.com

CCNT-050-032-015-MFBL

- high-current metering CTs
- medium-frequency transformers
- protective relay CTs
- ground-fault sensing
- high-current revenue-grade metering CTs
- medium-frequency isolation power transformers
- protection-class current transformers
- ground-fault/residual-current sensing cores